

## HCC

Bring the power of Hydrawise® to residential, commercial, and public-sector projects with this affordable powerhouse.

### KEY BENEFITS

- Number of stations: Conventional: 8 to 38 (plastic), 8 to 54 (metal and pedestal)\* With two-wire EZDS: up to 54 (all enclosure options)
- Standard programming option allows for 6 independent irrigation programs and 6 start times per program
- Advanced programming option provides station-based programming with up to 6 total start times available
- Any 2 programs or stations can operate simultaneously, providing more efficient watering
- 2 sensor inputs available for use with any Klik sensors and HC Flow Meter
- 1 P/MV output for pump start relay and master valve activation
- Wi-Fi enabled for quick connection to Hydrawise software
- 3 1/4" full-color touchscreen display for simple programming at the control panel
- Built-in milliamp sensor for wire fault detection and alerts



### OPERATING SPECIFICATIONS

- Transformer input: 120/230 VAC
- Transformer output (24 VAC): 1.4 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.56 A
- 2.4 GHz (only) Wi-Fi router compatible, 802.11 b/g/n 20 MHz
- Supported security protocols: WPA/WPA2 Personal (only), TLS
- Approvals: Plastic Wall Mount IP55 (outdoor), Plastic Pedestal IP24, Metal Wall Mount IP55, Metal Pedestal IP55 (outdoor), UL, cUL, FCC, CE, UKCA, RCM
- Warranty period: 2 years

### USER-INSTALLED OPTIONS

- Mini-Klik for rain sensor shutdown
- Wireless HC Flow Meter option permits wireless flow monitoring for Hydrawise enabled systems

Copyright © 2023 Hunter Industries™. All rights reserved.

<https://www.hunterindustries.com/en-metric/irrigation-product/hydrawise/hcc>  
082423